

# K1 GROUP

**K1**  
K1 Co.,Ltd.

412-0045 516-2 Kawashimada Gotenba City Shizuoka Japan  
[Https://www.k1-sks.com](https://www.k1-sks.com) TEL+81550-78-6182

*Aqua*  
Co.,Ltd.

410-0835 3-15 Nishijima-cho Numazu City Shizuoka Japan.  
[Https://www.aqua-bouhan-camera.com](https://www.aqua-bouhan-camera.com) TEL+81559-43-9592

## Aqua K1 Group Inc

58-B Saudi Arabia St. Better Living Subd. Brgy. Don Bosco  
Paranaque City 1711 Philippines. TEL+639172063134

SKS  
JAPAN



Satisfactory high performance and  
reasonably low price only for SKS

Made in "SKS"  
Original Network Camera  
Made in Japan

PROTECT  
YOUR  
LIFE





Satisfactory high performance and reasonably low price.  
More solid follow-up

Corporate crime prevention

Office Crime Prevention

Shop security

Home security

Over tens thousands of big hit cameras, Many achievements in security camera installation work at major companies, reliable support system.

(Available in languages, English, Japanese, Chinese, Korean, Tagalog)



### SKS-5004/SKS-5008/SKS-5016

#### Full HD digital recorder

Specialized for remote monitoring, viewing at breakthrough speeds (iOS, Android, PC) can be equipped with 2TB to 6TB HDD.

Recorder specification SKS-5000 series			
Model Name	5004	5008	5016
Video input	4ch BNC	8ch BNC	16ch BNC
Video output	1HDMI / 1VGA		
Codec	H.264		
Display	frame rate	120FPS	240FPS
	Resolution	1920×1080, 1440×900, 1280×1024, 1280×720, 1024×768	
Recording	Screen splitting	1,4	1,4,6,9
	frame rate	1920×1080/60FPS	1920×1080/120FPS
Available HDD	Up to 8TB per set	Up to 16TB in 2sets	
Search	type	Quick (2 minutes ~)/Calendar / Events / USB	
fast-forward speed		Up to 256x	
back up	device	USB/Net work	
File		DVR format	
Voice / Audio	Input / Output	4/1	2/1
PTZ(up,down,left,right) function		1RS-485/UTC Control	
UTC Ability to control OSD menu		OSD menu (camera illumination, white balance, etc.) & PTZ operation	
Net work Capabilities	interface	RJ45(10/100Mbps), Ethernet	
	protocol	DHCP, DDNS, PPPoE, UPNP	
	Soft ware	Web, Mobile, CMS	
	connection	Up to 16 people can connect simultaneously	
USB		2Place USB2.0	
Manipulation	Mouse	Mouse & Full Screen Button	
Language	Multilingual capability	Japanese, English, French, Korean, Russian, Turkish, German, Chinese, etc.	
Operating adaptive temperature		-10 to 55°C/10to90%humidity (non-condensing)	
power supply		DC12V3A	DC12V3A
Equipment Dimensions(mm)		257×222×45	320×261×52
Weight(without HDD)		0.74kg	1.32kg



### K-200BN

Affordable 2.4MP Full HD camera. A fixed lens for a wide field of view.

Camera specification K-200BN	
AHD Full HD imaging device	Dustproof and Waterproof Camera 2.4MP sony CMOS Images Sensor1/2.9
Total Pixels	2000(H) X 1241(V)
Operating system	progressive
resolution	1080P
output	ALL-HD (AHD/TVI/CVI/SD)
S/N Ratio	50dB or More (AGC Off)
Minimum illuminance	0.0001Lux / 0Lux (LED On)
Lens	3.6mm fixed
IR LED	Equipped with 6 10φ LEDs
shutter speed	4/25 - 1/50,000Sec
WDR	D-WDR (ON/OFF)
white balance	ATW / MWB
Day & Night	EXT / AUTO / COLOR / B/W
Operating temperature	-10~50°C / 10 to 90% RH
Color	White
Power supply	DC 12V (±10%)
Dimensions(mm)	64φ x 167.8(D)mm
weight	300g
	IP66



### SKS-S600BV-N

Adjustable lens supports zoom and wide angle. Even in the dark, people and cars are clearly recorded. Equipped with new technology STARVIS

Camera specification SKS-S600BV-N	
AHD Full HD imaging device	Dustproof and Waterproof Camera 2.4 MP Sony STARVIS CMOS 1/2.8
Total Pixels	2000(H) X 1241(V)
Operating system	progressive
resolution	1080P
output	ALL-HD (AHD/TVI/CVI/SD)
Day & Night	EXT / AUTO / COLOR / B/W
S/N Ratio	50dB or More (AGC Off)
Minimum illuminance	0.0001Lux / 0Lux (LED On)
Lens	varifocal manual lens 2.8-12mm
IR LED	24 high-spec SMD LEDs
shutter speed	4/25 - 1/50,000Sec
WDR	D-WDR (ON/OFF)
white balance	ATW / MWB
Operating temperature	-10 to 50°C / 10%~90% RH
Color	White
Power supply	DC 12V (±10%)
Dimensions(mm)	83(φ) x 254.5(D)mm
weight	約630g
	IP66



### SKS-S400DV

Can zoom from wide angle with adjustable lenses. Night vision is possible even in complete darkness.

Camera specification SKS-S400DV	
AHD Full HD imaging device	Not waterproof 2.4 MP Sony STARVIS CMOS 1/2.8
Total pixels	2000(H)X1241(V)
Operating system	progressive
resolution	1080P
output	ALL-HD (AHD/TVI/CVI/SD)
S/N Ratio	50dB or More(AGC Off)
Minimum illuminance	0.0001Lux/0Lux(LED On)
Lens	Varifocal manual lens 2.8~12mm
IR LED	Equipped with 30 5φ high-spec LED
shutter speed	4/25~1/50,000Sec
WDR	D-WDR(ON/OFF)
white balance	ATW/MWB
Day&Night	EXT / AUTO / COLOR / B/W
Operating temperature	-10to50°C / 10% to 90% RH
color	white
ATW/MWB	DC12V(±10%)
Dimensions(mm)	127φ×105(H)mm
weight	310g



### SKS-PTZ121IR

The best of remote controlled PTZ! Equipped with 6 ultra powerful infrared LEDs. Up, down, left, right zoom, and up to 220 locations for instant operation.

Camera specification SKS-PTZ121IR	
	IP66
Imaging device	2.4MP Sony CMOS image sensor 1/3
Total Pixels	2000(H) X 1241(V)
Operating system	progressive
Resolution	1080P
Output	Analog HD: 1080P
S/N Ratio	0dB or More (AGC Off)
Minimum illuminance	/0.0001Lux 0Lux (LED On)
Lens	x10zoom (5~50mm) Optical zoom
IR LED	New array IR LEDs
Focus	Autofocus / Trigger / Manual
2D DNR	0-5
White balance	Auto/ Full/ Fixed / Ttack1~4
Day&Night	AUTO / COLOR / B/W
Operating temperature	10-50°C / 10-90% RH
Color	White
power supply	DC12
Dimensions(mm)	215.3×200.8mm
weight	4.86kg
mirror function	Off / Lr / Up / Flip

\*noncondensing